



The Strong Ones



Standard 745 Series

Ultrasonic welding machine 35 kHz

The ultrasonic welding machine Standard 745 Series is suitable for welding operations of thermoplastic parts from small to medium size.





- Designed for the assembly into special purpose machines
- High process reliability
- Repeatable welding force
- Simple tool change and quick setup
- Integrated travel measurement with accuracy of ± 0.01 mm

Specification Standard 745 Series

Operating frequency:	35 kHz
Safety:	This ultrasonic welding machine conforms to CE standards and thus corresponds to the European safety requirements
Switches:	Two-hand start with EMERGENCY STOP at the front
Drive type:	Pneumatic double acting cylinder \varnothing 40 mm
Drive energy:	Compressed air supply: 7 bar maximum 6 bar nominal Maximum consumption at 6 bar: approx. 2.5 l _N /stroke
Maximum force:	745N at 6 bar compressed air
Maximum stroke:	100 mm
Weight:	30 kg without Generator
Throat depth:	170 mm from the centre line of the horn to the column
Height adjustment:	180 mm using height adjusting mechanism
Generator:	ADG35-400/600/900

Additional technical information available from Techspan on request.



TECHSPAN GROUP

Australia: Ph: 1-800 148 791 www.rincoultrasonics.com.au

New Zealand: Ph: ++64 9 827 6567 www.rincoultrasonics.co.nz