The Acoustic Ones

Standard Converters

Standard converters 70 kHz / 35 kHz / 20 kHz

The standard converters are suitable for the operation in standard machines and special actuators.

- Designed for the assembly into ultrasonic welding machines and special purpose machines
- The ideal Converter for every application thanks to an extensive range
- Heavy duty

Specification Converters

Operating frequency:	**C20-10/C20-12:**	**20 kHz**
	C35-10/C35-11/C35-12/C35-13:	**35 kHz**
	C70-2:	**70 kHz**
Weight:	**C20-10/C20-12:**	1.5 kg
	C35-10/C35-11/C35-12/C35-13:	300 g
	C70-2:	100 g
Generator:	Suitable for all types of the relevant frequency	
Housing:	**C20-10:** Closed steel housing	
	C20-12: Open steel housing	
	C35-10/C35-11: Closed steel housing	
	C35-12/C35-13: Open steel housing	
	C70-2: Closed steel housing	
Maximum temperature:	**50° C**	
	If used in continuous operation or with high temperatures, then air cooling should be used.	

Additional technical information available on request.

rinco ultrasonics

TECHSPANGROUP
Australia: Ph: 1-800 148 791 www.rincoultrasonics.com.au
New Zealand: Ph: ++64 9 827 6567 www.rincoultrasonics.co.nz

RINCO ULTRASONICS SWITZERLAND IS A CREST GROUP COMPANY